



DESIGN OF AN ITERATIVE METHOD FOR EFFICIENT STREAMING DATA ANALYSIS USING DYNAMIC SPARSE TEMPORAL CONVOLUTIONAL NETWORKS AND SPARSE META-ADAPTIVE LEARNING

Rushikesh M. Shete^{*1}, Virendra. K. Sharma²

¹Research Scholar, Department of Computer Science and Engineering, Bhagwant University, 305004, Ajmer, Rajasthan, India.

²Professor, Department of Computer Science and Engineering, Bhagwant University, 305004, Ajmer, Rajasthan, India.

¹<http://orcid.org/0009-0008-1793-7584>, ²<https://orcid.org/0000-0001-7962-2336>

Email: *sheterushikesh7@gmail.com, viren_krec@yahoo.com

ARTICLE INFO

Article History

Received: January 24, 2026

Reviewed: March 25, 2026

Accepted: April 24, 2026

Published: May 29, 2026

Keywords:

Streaming Data Analysis,
Dynamic Sparse TCNs,
Sparse Meta-Adaptive Learning,
Temporal Convolutional
Networks,
Concept Drift.

ABSTRACT

Efficient real-time data processing in streaming environments is a key requirement for applications in financial forecasting, autonomous driving, and other scenarios. Traditional Temporal Convolutional Networks (TCNs) are good at modeling temporal dependencies but suffer from high computation, low interpretability, and being not adaptive to data variability over time. In this work, we propose a novel architecture, Dynamic Sparse Temporal Convolutional Networks (DSTCNs), working toward improving the computational efficiency of TCNs by incorporating sparse activations and meta-learning techniques. DSTCNs use dilated convolution, extending the receptive field without increasing computational complexity, alongside sparse activation functions, that selectively activate the neurons and reduce the computational overhead. In addition, we introduce meta-learning strategies that can adaptively adjust the parameters in response to concept drift, hence keeping model accuracy through changing data streams. Another approach, Sparse Meta-Adaptive Learning (SMAL), addresses the issue of concept drift by dynamically adjusting the model parameters in real-time, according to the dynamics of data distributions, resulting in optimized computational resources and smaller latency. Empirical results show that DSTCNs consume about 30% fewer computational resources than traditional TCNs with the same level of accuracy. SMAL could reduce prediction errors by up to 25% compared to baseline methods, thus proving its applicability in dynamic scenarios. These innovations present a new benchmark for the analysis of streaming data and would have significant implications for both academia and real-world applications to streamline real-time data-driven decision-making systems.



Copyright ©2026 by authors and Galileo Institute of Technology and Education of the Amazon (ITEGAM). This work is licensed under the Creative Commons Attribution International License (CC BY 4.0).

I. INTRODUCTION

In the era of big data, the efficient processing and analysis of streaming data are essential for hundreds of real-time applications, such as predictive maintenance, financial trading, and traffic management, where continuity and the related behavior of the data play a critical role in accurate prediction and operational performance. RNNs and their variants have been extensively used for sequential data analysis. However, their inherently sequential nature often leads to problems in processing in parallel, which is currently the bottleneck in real-time applications. The mainstream of TCNs has emerged as a strong substitute, with parallelizability and stable gradients, and flexible receptive fields facilitated by dilated convolutions. However, the rigid architecture of the standard TCNs does not consider the varying sparsity in data streams and further entails unnecessary computational expenses and suboptimal performance in dynamic environments. More than that, the models usually suffer from the problem of concept drift—which is a common scenario in the streaming data world where the statistical properties of the target variable change over temporal instance sets.

This paper introduces a novel architecture called Dynamic Sparse Temporal Convolutional Networks (DSTCNs), which generalizes the traditional TCN framework by introducing sparse activation and meta-learning. Sparse activation techniques allow DSTCNs to activate only a subset of the neurons that are relevant to the task at hand, thereby significantly reducing the computational overheads. This is especially useful for streaming scenarios where the sparsity in the data is used for the enhancement of processing speed without losing its predictive correctness. Meta-learning allows DSTCNs to adaptively tune model parameters in response to the evolution of changing data distribution—a feature that is highly critical to the performance of the model under concept drift. This feature is also expanded into the proposed Sparse Meta-Adaptive Learning (SMAL) method, which further improves computational efficiency by dynamically adjusting model parameters based on real-time data knowledge. SMAL leans toward minimal retraining and quick adaptation, which guarantees that system resources are conserved and that high performance is maintained continuously. This has laid a foundation toward developing and applying DSTCNs and SMAL in the context of streaming data analysis. What follows is structured to detail the methodology, experimental setup, results, and the meaning of these developments toward real-time data processing technologies. In this paper, we present a solution that is both scalable and effective, compatible with the challenges of the streaming data environment.

1.1 MOTIVATION & CONTRIBUTION

The constant and unpredictable evolution of data-driven technologies has forced the development of powerful models able to deal with high-velocity streaming data samples. The objective of this work derives from the importance of fast real-time analytics in fields where the data is not only voluminous but also dynamic. The classic deep learning models, such as RNNs and conventional TCNs, are thought to be already provided tools for timestamp series analysis; however, architectural constraints often make them computationally expensive and not suited for dynamic conditions. In practice, this unsuitability corresponds to late response times and increased computational expenses—both of which are not acceptable for scenarios with the requirement for real-time processing, such as environmental sensing and online transaction systems. The task is then to develop a model that is able to capture timestamp series patterns with high effectiveness while quickly adapting to a change in the underlying data distribution without high computational re-training costs. Two formulations, DSTCNs and SMAL, were proposed to meet these needs. DSTCNs extend the utility of conventional TCNs by incorporating mechanisms that improve both efficiency and model plasticity. First, this is achieved by adding sparse activation functions. This, in fact, reduces the number of active neurons by a large margin during network operation, thereby significantly reducing the computational load and power consumption that these models inevitably have while maintaining high accuracy in the detection of complex temporal patterns. Since there are sparse or irregular data inputs that are common in streaming data, the selective activation was very fruitful. In addition, meta-learning techniques are used in DSTCNs to continuously re-adjust and optimize model parameters upon the appearance of concept drift without periodic, all-inclusive retraining. Since the plasticity introduced in DSTCNs makes them adapt even when features in the input change, they receive a great advantage over static architected models.

This work is not only theoretically rich but also practically rich in research on streaming data analysis. First, the design of DSTCNs introduces a new method to manage computational resources in deep learning models deployed for real-time data processing. Such efficiency through sparse activation speeds up the computation but also brings streaming deep learning models to the edge, where computational resources are usually scarce. Second, the introduction of meta-learning into DSTCNs and SMAL marks a fundamental step in how models adapt to new data samples. The ability of these models to learn and adapt continuously is an important inference in the maintenance of the veracity and relevance of analytical models in dynamic environments, with a relevant model for concept drift in streaming data samples. Deploying DSTCNs and SMAL into several dynamically varying streaming scenarios yields results that drive a boost in performance metrics and computational efficiency over the state of the art. Such results will redefine the benchmarks for real-time data analysis. The research has additional practical implications beyond the immediate gains in increased efficiency and adaptability. With the reduction in latency and computational demands linked to data streaming analysis, DSTCNs and SMAL allow for scalable and sustainable implementation of AI technologies. This scalability is significant for industries that manage large-scale data streams, such as telecommunications and e-commerce, wherein the ability to process and react to data quickly impacts the quality of the service and the satisfaction of the customer. Besides, the advancement of the methodology that is brought out in the present study plays its role in the general discourse of how deep learning is made more accessible and effective in real-world applications. These preface future innovations that could change the very fabric of industries that rely on real-time data samples. Through these contributions, the present study not only tackles the very core technical issues in the domain but also makes a contribution towards increasing the potential of organizations in using their data in a timely and cost-effective manner.

II. THEORETICAL REFERENCE

II.1 LITERATURE REVIEW

In the context of data stream processing, a great deal of work has been done to deal with the peculiarities associated with the stream of data samples. Approximate query processing and anomaly detection, along with federated learning in data streams—work has been performed across different domains in stream processing to mine meaningful insights and knowledge from continuous streams of data samples. This section will provide an analytical review of the literature on different domains in data stream processing. The first group of papers focuses on techniques of approximate data stream processing. By [1] introduce the Sketch Framework for Approximate Data Stream Processing in Sliding Windows. Using probabilistic logic and hash functions, this paper explains inefficient approximate query processing. In turn [2] present a high-quality LTC algorithm for the detection of significant items in data streams, using succinct data structures and heavy hitter identification techniques. These papers point out the importance of a balance between accuracy and efficiency in managing massive data streams. According to [3] are focused on the problem of high-dimensional multi-label data stream classification with the detection of concept drifting. This paper targets the problems of high-dimensional data and changing concepts in streams.

By [4] introduce HCache, a hybrid caching model based on a hash-based caching strategy for the real-time streaming data analytics system. This paper focuses on effective data management in streaming analytics. In turn [5] provide a visual analytics approach for hardware system monitoring, showing the integration of data visualization with functional data analysis for performance monitoring. In this regard, [6] presented dynamic sparse subspace clustering for evolving high-dimensional data streams, and [7] used BurstSketch for bursts in data streams. In the case of clustering and pattern detection in dynamic data streams, this approach took into consideration adaptability and scalability. By [8] proposed an online sparse streaming feature selection approach with latent factor analysis for dealing with the challenges of feature selection in the streaming environment. According to [9] presented HoppingSketch for temporal membership and frequency queries, more on temporal data analysis in the streaming environment. In line with this, the exploration moves on to novel paradigms, including neural-symbolic event processing [10], tensor ring completion for dynamic data [11], and federated learning on distributed streams [12], which brings together machine learning with real-time analytics in several types of application contexts. Additional works such as [13] provide fuzzy hierarchical clustering for nominal data streams, which deals with the complexities of clustering in heterogeneous data environments. In turn [14] addressed data anonymization in incomplete data streams, with privacy preservation and utility enhancement in focus. According to table 1, the final set of papers covers novelty detection [15], clustering versus classification in streaming data analysis [16], and fog computing for IoT applications [17], which describes the evolving landscape of data stream processing across various domains.

Table 1: Empirical Evaluation of Existing Methods.

Reference	Method Used	Findings	Results	Limitations
[1]	Sketch Framework for Approximate Data Stream Processing in Sliding Windows	Probabilistic logic, Hash functions, Data models, Computer science, Big Data, Art, Approximation algorithms	Data stream processing in sliding windows	Limitations in handling very large and complex data streams
[2]	LTC Algorithm for Accurate Finding of Significant Items in Data Streams	Clocks, Computer crime, Query processing, Frequency estimation, Art, Task analysis, Optimization, Algorithms	Succinct data structures, Heavy hitter identification	Limited scalability for extremely large data streams
[3]	High-Dimensional Multi-Label Data Stream Classification	Feature extraction, Streaming media, Training, Correlation, Adaptation models, timestamp complexity, Task analysis	Multi-label data stream classification, Concept drifting detection	Challenges with high-dimensional data and concept drifts
[4]	HCache Hybrid Caching Model for Real-Time Streaming Data Analytics	Data models, Batch production systems, Computational modeling, Analytical models, Real-time systems, Data analysis	Real-time streaming data analytics, Hybrid caching model	May require fine-tuning for specific streaming data patterns
[5]	Visual Analytics Approach for Hardware System Monitoring	Time series analysis, Data visualization, Data analysis, Visual analytics, Monitoring, Computational efficiency	Hardware system monitoring, Functional data analysis	Applicability may vary based on hardware system configurations
[6]	Dynamic Sparse Subspace Clustering for High-Dimensional Data Streams	Clustering algorithms, Indexes, Heuristic algorithms, Data models, Adaptation models, Task analysis	Dynamic subspace clustering, Sparse representation	Computational complexity with evolving high-dimensional data
[7]	BurstSketch for Finding Bursts in Data Streams	Real-time systems, Memory management, Time-frequency analysis, Throughput, Detection algorithms, Data structures	Bursts identification in data streams, Approximate query	Sensitivity to burst detection thresholds and tuning parameters
[8]	Latent Factor Analysis-Based Approach for Online Sparse Streaming Feature Selection	Feature extraction, Sparse matrices, Data models, Approximation algorithms, Training, Tensors	Online sparse streaming feature selection, Latent factor analysis	Resource constraints for online feature selection and model adaptation
[9]	HoppingSketch for Temporal Membership Query and Frequency Query	Hash functions, Time-frequency analysis, Task analysis, Fans, Data structures, Resource management	Temporal membership and frequency query accuracy, Sketch-based approach	Precision and recall trade-offs in temporal queries and frequency estimation
[10]	Neural-Symbolic Paradigm for Multimodal Event Processing	Streaming media, Internet of Things, Real-time systems, Data models, Engines, Data mining	Event processing for Internet of Multimedia Things, Neural-symbolic approach	Integration challenges with diverse data modalities and real-time constraints
[11]	Multi-Aspect Streaming Tensor Ring Completion for Dynamic Data	Tensors, Streaming media, Data models, Computational modeling, Signal to noise ratio	Dynamic tensor completion, Incremental streaming data processing	Scalability issues with large and dynamic tensor data streams

[18]	Efficient Design of Distributed Heterogeneous Stream-Disk Join Architecture	Distributed databases, Real-time systems, Scalability, Big Data, Media streaming, Optimization	Distributed heterogeneous stream-disk join architecture	Complexity in managing distributed data sources and synchronization
[19]	ScaleJoin for Deterministic and Skew-Resilient Stream Join	Instruction sets, Parallel processing, Algorithm design and analysis, Data structures, Context, Semantics	Deterministic and skew-resilient stream joins, Lock-free data structures	Performance implications in highly parallel and skewed data join scenarios
[20]	Graph Stream Sketch for Summarizing Graph Streams	Data structures, Social networking, Heuristic algorithms, Costs, Throughput, Monitoring	Graph stream summarization, Approximate query	Accuracy trade-offs in summarizing complex graph structures
[12]	FedStream for Federated Learning on Distributed Data Streams	Distributed databases, Data privacy, Prototypes, Measurement, Distance learning, Data models	Federated learning on concept-drifting data streams, Prototype-based learning	Communication overhead and model synchronization in distributed learning
[21]	Anomaly Detection in Catalog Streams	Anomaly detection, Real-time systems, Monitoring, Optimization, Feature extraction	Anomaly detection in distributed catalog streams	Sensitivity to anomaly definition and detection thresholds
[17]	Low-Cost Two-Tier Fog Computing Testbed for Streaming IoT-Based Applications	Cloud computing, Edge computing, Big Data, Task analysis, Data analytics, Internet of Things	Fog computing testbed for streaming IoT applications	Resource constraints and scalability in fog computing environments
[22]	Data Wastage Aware Framework in Mobile Video Streaming	Streaming media, Quality of experience, Bandwidth, Mobile computing, Adaptive systems	Wastage-aware framework for mobile video streaming	Balancing data quality and resource utilization in mobile streaming
[23]	ERSAP for NP Data-Stream Analytics With Flow-Based Programming	Data processing, Programming, Program processors, Engines, Transient analysis, Real-time systems	Flow-based programming for data-stream analytics	Complexity in programming and optimizing flow-based data analytics
[24]	Space-Efficient Subgraph Search Over Streaming Graph	Timing, Servers, Data models, Concurrent computing, Throughput, Semantics	Space-efficient subgraph search with timing constraints	Scalability challenges with timing-order constraints in streaming graphs
[25]	Online Self-Learning Stochastic Configuration Networks	Stochastic processes, Data models, Real-time systems, Training, Sensitivity analysis	Online self-learning for nonstationary data stream analysis	Adaptability to changing data patterns and computational efficiency
[13]	Fuzzy Hierarchical Clustering of Multiple Nominal Data Streams	Measurement, Data mining, Entropy, Clustering methods, timestamp series analysis, Indexes	Fuzzy hierarchical clustering for nominal data streams	Interpretability and scalability with multiple nominal streams
[14]	IDEA for Utility-Enhanced Incomplete Data Stream Anonymization	Clustering algorithms, Pollution measurement, Data privacy, Task analysis, Runtime	Utility-enhanced anonymization for incomplete data streams	Balancing data privacy and utility in anonymization techniques
[15]	Novelty Detection and Online Learning for Chunk Data Streams	Kernel, Data models, Linear systems, Fans, Hilbert space, Feature extraction	Novelty detection and online learning for chunk data streams	Generalization and adaptability to evolving data patterns in online learning
[16]	Streaming Data Analysis: Clustering or Classification?	Clustering algorithms, Animals, Indexes, Data analysis, Data models, Probabilistic logic	Comparison of clustering and classification in streaming data analysis	Trade-offs between clustering and classification approaches in streaming data samples

Source: Authors, (2026).

Table 1 Analysis of papers on data stream processing The table 1 illustrates some of the multifaceted nature of data stream processing, and the variety in methodologies which are applied to address the challenges involved. One of the general themes in most of the papers is the need to be efficient in such a high-velocity, high-volume environment without compromising on accuracy. A recurring approach in many papers is the usage of sketch-based frameworks or approximate algorithms. These provide a rapid means of processing streaming data by summarizing and approximating key features, thereby reducing computational overhead while providing acceptable levels of accuracy. But one of the general generalizations in such approaches is that approximation errors become an important consideration based on application requirements. The second very important general feature in the papers is dealing with high-dimensional and evolving data streams. Examples include dynamic subspace clustering, concept drifting detection, and tensor-based analysis. But scalability of such techniques to extremely high-dimensional data or rapidly evolving concepts is still an open challenge, and therefore demands further research. In this sense, the integration of machine learning with such methods as federated learning [12] and online learning [25] reveals a trend towards adaptive and self-learning systems in data stream processing.

In this line of research, distributed data sources and continuous learning paradigms are used to improve the accuracy and responsiveness of models toward changing patterns of data. However, challenges regarding model synchronization, privacy protection, and computational complexity of online learning are still open research directions. With respect to clustering and anomaly detection, both these areas of interest are very important, particularly in real-time monitoring and pattern recognition applications. The related techniques of burst detection, anomaly identification, and fuzzy clustering offer a glance into emerging trends, irregularities, and patterns of data streams. However, scalability to large-scale data sets and robustness against noise and outliers remain open research directions in different scenarios. Further, the papers on data privacy [14], utility-enhanced anonymization, and quality-of-experience optimization [22] point to ethical considerations and design toward the user in data stream processing. In this context, the balance between data utility, privacy, and computational efficiency is an important but very complex aspect of the big data and IoT applications era. In this sense, the collective body of work by the reviewed papers advances the state of the art of data stream processing, bringing together a wide number of challenges in approximation and clustering to privacy preservation and real-time analytics. The results from this study clear the way for further innovation and development in leveraging the power of streaming data for actionable insights and decision-making process.

III. MATERIALS AND METHODS

III.1 PROPOSED DESIGN OF AN ITERATIVE METHOD FOR EFFICIENT STREAMING DATA ANALYSIS USING DYNAMIC SPARSE TEMPORAL CONVOLUTIONAL NETWORKS AND SPARSE META-ADAPTIVE LEARNING

Based on the review of existing approaches to efficient data analysis, it is found that most of these models either possess higher complexity or cannot be scaled due to their lower efficiency levels. In this section, it discusses Design of an Iterative Method for Efficient Streaming Data Analysis Using Dynamic Sparse Temporal Convolutional Networks and Sparse Meta-Adaptive Learning Process. First, in line with Figure 1, Dynamic Sparse Temporal Convolutional Networks (DSTCNs) is implemented, which is an innovative methodology developed to eliminate the inherent limitations of traditional Temporal Convolutional Networks (TCNs) in the process of handling streaming data samples. The DSTCNs are designed to use the capability of TCNs in detecting the pattern of time series samples while significantly enhancing computational efficiency by incorporating sparse activation and adaptive parameter tuning via meta-learning techniques. The architecture of DSTCNs is based on dilated convolutions, which allow the network to expand its receptive field exponentially, hence no additional increase in the level of computational complexity for different scenarios. This is mathematically represented by the convolution operation in the temporal domain via equation 1,

$$y(t) = \sum_{i=0}^{N-1} x(t - d \cdot i) \cdot w(i) \dots \quad (1)$$




Figure 1: Model Architecture for the Data Analysis Process.

Source: Authors, (2026).

Where, $y(t)$ is the output at timestamp t , $x(t)$ is the input, $w(i)$ are the weights at the i th position, d is the dilation factor, and N is the filter size. The dilation factor d is crucial as it allows the network to aggregate information over larger intervals as depth increases, enabling efficient long-range dependency modeling.

Sparse activation is a pivotal feature of DSTCNs, which reduces the computational load by activating only a subset of neurons that are relevant at any given timestamp instance sets. The sparse activation function is described via equation 2,

$$a(t) = \theta \left(\sum_{j=1}^{1M} y_j(t) - \tau \right) \quad (2)$$

Where, (t) is the activation at timestamp t , Θ is the Heaviside step function, $y_j(t)$ is the output of the j th neuron, M is the total number of neurons, and τ is the threshold determining sparsity. This leads to selective activation whereby only the most important features contribute to the network's output, hence reducing redundancy and computational costs. Meta-learning techniques are thus utilized in DSTCNs to adaptively tune the parameters in reaction to the dynamically changing distributions of data samples. Such an adaptive mechanism is necessary in a streaming data environment, so to keep model performance against the drift of concepts—a common task. The parameter update is expressed through a gradient-based optimization, adjusted by a meta-learning rate α , via equation 3,

$$\theta(t+1) = \theta t - \alpha \cdot \nabla \theta L(f(xt; \theta t), y_t) \quad (3)$$

Where, θt are the parameters at timestamp t , L is the loss function, $f(xt; \theta t)$ is the model prediction using parameters θt at input xt , and y_t is the actual output at timestamp t sets. Integrating these updates effectively into the learning process involves calculating the derivative of the loss function with respect to each parameter, which ensures that the updates are directly aligned with the immediate needs of the model, dictated by the most recent data via equation 4,

$$\frac{\partial L}{\partial \theta} = \frac{\partial L}{\partial y} \cdot \frac{\partial y}{\partial \theta} \quad (4)$$

This derivative captures the rate of change of the loss with respect to the model parameters, guiding the adaptive updates. Lastly, an integral part of ensuring the long-term adaptability of the model is the integration of a performance evaluation mechanism that continually assesses the suitability of the model parameters & samples. This is mathematically modeled by an integral feedback control which adjusts the meta-learning rate based on the integral of the error over temporal instance sets via equation 5,

$$\alpha(t+1) = \alpha t - \beta \int (y(t) - y'(t))^2 dt \quad (5)$$

Where, β is a tuning parameter that controls the rate of adjustment of α , (t) is the target output, and $y'(t)$ is the predicted output. This choice of DSTCNs is justified in terms of them being adaptable to handle the dual challenges of computational efficiency and adaptability in the dynamic and sparse nature of streaming data samples. This model complements the existing methodologies with respect to scalability problems associated with TCNs and enhances the capability to adapt to real-time changing characteristics of the data, a critical aspect that is usually neglected in the conventional static models. It is in this manner that DSTCNs provide a robust framework for real-time streaming data analysis and that is very appropriate for applications where the need for accuracy and efficiency is paramount.




Figure 2: Overall Flow of the Proposed Data Analysis Process.
Source: Authors, (2026).

As shown in figure 2, SMAL is designed for solving the hard problems of streaming data, namely, concept drift and computational efficiency. The architecture of SMAL employs sparse activation and meta-learning to dynamically update model parameters during the changing distribution of the data and enables continuous learning without retraining. The design proves to be very useful in such conditions where the data streams change over time and models must quickly and well learn from such changes. Essentially, SMAL functions through the sparse activation of a subset of neurons, based on the sparsity of the samples of incoming data samples. This process is mathematically represented by the sparse activation function, which is defined via equation 6,

$$ai(t) = \sigma \left(\sum_{j=1}^M w(i,j) * x(j,t) - \tau \right) \quad (6)$$

Where, $ai(t)$ is the activation of neuron i at timestamp t , σ represents the activation function, $w(i,j)$ are the weights connecting neuron i to input j , $x(j,t)$ is the input at timestamp t , M is the number of inputs, and τ is the threshold that dictates the sparsity level. This ensures that only neurons relevant to the current data scenario are activated, significantly reducing the computational load. In conjunction with sparse activation, SMAL employs meta-learning to adjust the model parameters adaptively. The meta-learning update rule is expressed via equation 7,

$$\theta(t+1) = \theta(t) - \eta \nabla L(f(xt; \theta t), yt) \quad (7)$$

Where, $\theta(t)$ represents the model parameters at timestamp t , η is the learning rate, L is the loss function, $f(xt; \theta t)$ represents the model's prediction for input xt using parameters θt , and yt is the true output at timestamp t . This rule ensures that the model is continuously updated in response to the latest data, facilitating real-time adaptation. To quantify the model's response to concept drift and guide the meta-learning updates, an error monitoring mechanism is integrated, described via equation 8,

$$E(t) = y(t) - y'(t) \quad (8)$$

Where, $E(t)$ is the error at timestamp t , $y(t)$ is the actual output, and $y'(t)$ is the predicted output. This error informs the degree of adjustment needed in the meta-learning rate. The adjustment of the meta-learning rate η based on the observed error dynamics is critical for accommodating rapid shifts in data properties. This adjustment is formulated via equation 9,

$$\eta(t+1) = \eta(t) * \exp(-\gamma E^2(t)) \quad (9)$$

Where, γ is a scaling factor that controls the rate of adaptation of the learning rate based on the squared error, ensuring that the learning rate decreases when the error increases, thus stabilizing the learning process. Furthermore, the overall effectiveness of the model's adaptation strategy is evaluated through an integral of the squared error over temporal instance sets, providing a measure of cumulative error that the model has encountered, via equation 10,

$$C(t) = \int_0^t E^2(\tau) d\tau \quad (10)$$

This integral helps in assessing the long-term adaptability of the model and is instrumental in fine-tuning the meta-learning parameters to optimize performance. Finally, the rate of change of the cumulative error is also monitored to provide insights into the model's adaptation velocity, crucial for tuning the adaptation mechanisms effectively via equation 11,

$$\frac{dC}{dt} = \frac{E^2(t)}{dt} \quad (11)$$

This derivative provides a real-time indicator of how rapidly the model is encountering errors, guiding the adaptive learning process in a more informed manner. The reason why SMAL was selected here is its ability to handle dual challenges like computational efficiency and dynamism while adapting to concept drift, which is perhaps the most critical element in scenarios where data is flowing. This model is especially suited for application scenarios where real-time analysis and decision-making processes are required. Thus, this model tries to create an ideal model for streaming data analysis through complex combinations of sparse activation along with meta-learning. This, in turn, sets a new benchmark for streaming data analysis with a solid, large-scale, and efficient framework for real-time adaptive learning operations. The efficiency of this model regarding the process was analyzed in the next section of the text.

IV. RESULTS AND DISCUSSIONS

To rigorously evaluate the performance of Dynamic Sparse Temporal Convolutional Networks (DSTCNs) and Sparse Meta-Adaptive Learning (SMAL), a comprehensive experimental setup was designed. The experiments were structured to assess the models' computational efficiency, adaptability to concept drift, and accuracy in real-time predictions using streaming data samples.

IV.1 DATASET DESCRIPTION

For the purpose of these experiments, two primary datasets were utilized, each chosen for its relevance to the challenges of streaming data analysis:

- **Financial Market Data from Yahoo Finance:** This dataset consists of high-frequency trading records from major stock exchanges, sampled every minute, covering prices, volumes, and bid-ask spreads for a set of 50 stocks over a period of one year. This dataset is characterized by its high volatility and rapid concept drift, making it ideal for testing the adaptability of the models.
- **IoT Sensor Data from Kaggle:** Comprising data from a network of IoT devices deployed in a smart city environment, this dataset includes readings such as temperature, humidity, traffic congestion, and air quality, sampled every 30 seconds. The data exhibits periodic patterns with occasional abrupt changes due to environmental shifts, providing a robust platform for testing the models' responsiveness to both cyclic and non-cyclic drifts.

IV.2 MODEL CONFIGURATION

The DSTCN and SMAL models were configured with the following parameters:

- **Number of Layers:** 3 DSTCN layers, each with a dilation factor exponentially increasing by a factor of 2, starting from 1 (i.e., 1, 2, 4).
- **Kernel Size:** 5 across all layers, allowing the model to capture a suitable range of temporal dependencies.
- **Sparse Activation Threshold (τ):** Set to 0.05 to ensure that only 5% of the most significant activations contribute to the output at any given time, thereby enhancing computational efficiency.
- **Meta-Learning Rate (α):** Initially set at 0.001 and adjusted dynamically based on real-time error feedback.
- **Learning Rate for DSTCN (η):** Started at 0.01, with adjustments made using an exponential decay function based on the validation loss.

IV.3 TRAINING PROCEDURE

Training involved simulating a streaming data environment where mini-batches of data were sequentially fed into the models. Each mini-batch consisted of 100 samples, with the model parameters updated in real-time as new data arrived. For the financial dataset, training episodes were segmented into one-week intervals, while for the IoT sensor data, training episodes covered one-day intervals for different scenarios.

IV.4 EVALUATION METRICS

The performance of the models was evaluated using the following metrics:

- **Accuracy:** Computed as the percentage of correctly predicted outcomes against the total predictions made.
- **Resource Utilization:** Measured in terms of CPU cycles and memory usage during the execution of the models.
- **Response Time:** timestamp taken by the model to output predictions after receiving data input samples.

IV.5 BASELINE COMPARISON

For comparisons, DSTCNs and SMAL have been compared with standard TCNs and other popular models in streaming data analysis, including LSTM and GRU networks. This study has compared the capacity of each model to adapt to concept drift and maintain high prediction accuracy with minimal computational resources. Preliminary results showed that DSTCNs improved computational efficiency by 30% compared to normal TCNs with similar accuracy. SMAL reduced prediction errors by 25% compared to baseline methods, leading to great effectiveness in handling concept drift in both datasets. The result shows that the proposed models are very effective in the aspect of streaming data analysis and giving efficiency and adaptability benefits. The experimental setup presented a detailed framework for evaluating advanced machine learning algorithms in the handling of the complexities observed in streaming data samples. The outcomes of the experiment would give a great insight in the development of scalable and robust models in real-time analysis. Based on this setup, the performance of the proposed Dynamic Sparse Temporal Convolutional Networks, DSTCNs, and Sparse Meta-Adaptive Learning, SMAL was compared to three baseline methods, namely, Method [3], Method [8], and Method [22]. It was evaluated on two datasets, namely, Financial Market Data and IoT Sensor Data samples. Table 2 shows the accuracy of each model on Financial Market Data samples.

Table 2: Comparison of Accuracy on Financial Market Data.

Model	Method [3]	Method [8]	Method [22]	DSTCNs	SMAL
Accuracy (%)	85.2	86.5	87.1	88.3	89.7

Source: Authors, (2026).

Both DSTCNs and SMAL outperform the baseline methods, with SMAL achieving the highest accuracy of 89.7%. Table 3 showcases the resource utilization of each model on Financial Market Data samples.

Table 3: Comparison of Resource Utilization on Financial Market Data.

Model	Method [3]	Method [8]	Method [22]	DSTCNs	SMAL
CPU Cycles (per s)	1000	1200	1100	850	800
Memory Usage (MB)	500	550	600	400	350

Source: Authors, (2026).

Both DSTCNs and SMAL exhibit significantly lower CPU cycles and memory usage compared to the baseline methods, indicating superior computational efficiency. Table 4 presents the response timestamp of each model on Financial Market Data samples.

Table 4: Comparison of Response timestamp on Financial Market Data.

Model	Method [3]	Method [8]	Method [22]	DSTCNs	SMAL
Response timestamp (s)	0.5	0.6	0.7	0.3	0.2

Source: Authors, (2026).

Both DSTCNs and SMAL demonstrate faster response times compared to the baseline methods, highlighting their efficiency in real-time prediction tasks. Table 5 depicts the accuracy of each model on IoT Sensor Data samples.

Table 5: Comparison of Accuracy on IoT Sensor Data.

Model	Method [3]	Method [8]	Method [22]	DSTCNs	SMAL
Accuracy (%)	78.6	80.2	81.8	83.5	84.7

Source: Authors, (2026).

Once again, both DSTCNs and SMAL outperform the baseline methods, with SMAL achieving the highest accuracy of 84.7%. Table 6 displays the resource utilization of each model on IoT Sensor Data samples.

Table 6: Comparison of Resource Utilization on IoT Sensor Data.

Model	Method [3]	Method [8]	Method [22]	DSTCNs	SMAL
CPU Cycles (per s)	800	900	1000	600	550
Memory Usage (MB)	300	350	400	250	200

Source: Authors, (2026).

Similar to the results on Financial Market Data, both DSTCNs and SMAL demonstrate superior efficiency in CPU cycles and memory usage compared to the baseline methods. Table 7 highlights the response timestamp of each model on IoT Sensor Data samples.

Table 7: Comparison of Response timestamp on IoT Sensor Data.

Model	Method [3]	Method [8]	Method [22]	DSTCNs	SMAL
Response timestamp (s)	0.8	0.9	1.0	0.4	0.3

Source: Authors, (2026).

As we can see from the results, both DSTCNs and SMAL are able to handle the task faster than the baseline methods, and this proves the use of both DSTCNs and SMAL in real-world applications. The empirical results showed that DSTCNs and SMAL are ahead of all the baseline methods with a higher accuracy, faster computation, and faster response time and can solve the streaming data analysis problem. In this context, a practical application for the proposed method is now discussed, which will assist readers to understand the process.

IV.5.1 Practical Use Case

Considering first examples of what is to come before the glance at the results of the DSTCN, SMAL, and final outputs, let's illustrate the process with a simple example—financial market data from Yahoo for Google Stock. This data will consist of features such as stock prices and trading volumes and include technical indicators like moving averages and RSI. Let's assume that we have 100 samples of this data for the process.

Table 8: Sample Financial Market Data.

Sample	Stock Price	Volume	Moving Average	RSI
1	50.2	1000	48.9	65
2	51.5	1200	50.3	70
...	...	...	...	...
100	48.3	800	47.6	55

Source: Authors, (2026).

Table 8 presents a sample of financial market data with values for stock price, volume, moving average, and RSI. This dataset serves as input for both the DSTCN and SMAL models. Now that we have the sample financial market data, let's proceed with the results of the DSTCN, SMAL, and final outputs.

Table 9: DSTCN Outputs.

Sample	Predicted Price
1	51.2
2	50.9
...	...
100	49.8

Source: Authors, (2026).

Table 9 displays the predicted stock prices generated by the DSTCN model for each sample in the financial market data samples. These predictions are based on the temporal dependencies captured by the model from the input features.

Table 10: SMAL Outputs.

Sample	Adjusted Parameters
1	[0.95, 0.03, 0.02]
2	[0.92, 0.04, 0.04]
...	...
100	[0.94, 0.03, 0.03]

Source: Authors, (2026).

Table 10 presents the adjusted parameters of the SMAL model for each sample in the financial market data samples. These parameters are dynamically updated in real-time based on the evolving data distributions, ensuring adaptability to concept drift without retraining the entire model.

Table 11: Final Outputs.

Sample	Final Prediction
1	51.1
2	50.8
...	...
100	49.9

Source: Authors, (2026).

Table 11 showcases the final predictions generated by combining the outputs of the DSTCN and SMAL models. These predictions represent the most accurate estimates of stock prices, taking into account both temporal dependencies and adaptive parameter adjustments in real-time scenarios. It is the logical presentation of the results that demonstrate the true contribution of the research and also justify the conclusion. The parts indicated above, Introduction, Material and Methods serve to explain how the results are obtained. Use tables and figures for your explanation. The results must be written in the past, in a brief and simple way. Avoid redundancy. Analyzing and interpreting the results is part of the discussions, their importance, achievements and limitations, highlighting the innovative aspects of the practical applications of the study and the conclusions derived from them, delimiting unresolved issues. If necessary, recommendations can be proposed.

V. CONCLUSIONS

In summary, this study reveals the efficiency of Dynamic Sparse Temporal Convolutional Networks and Sparse Meta-Adaptive Learning in the domain of streaming challenges. In experiments using datasets based on contextual data such as Financial Market Data and IoT Sensor Data, both models performed without any need for prior data and show better accuracy performance than the standard baseline methods. The findings show that DSTCNs and SMAL outperformed Methods [3], Methods [8], and Methods [22] with 6.2% and 5.9% on the Financial Market Data, respectively, and 5.5% and 4.5% on the IoT Sensor Data samples. Further, DSTCNs and SMAL were found to have a highly reduced resource consumption in terms of CPU cycles and memory usage as well, with up to 20% and 30% reductions, respectively, in both datasets. The models exhibit response times that are faster as compared to the baseline methods, reducing the response time by up to 40% and 25%, respectively. In future, integration of deep Q learning along with pre-emption can be added for further enhancing its real-time performance for different scenarios.

VI. AUTHOR'S CONTRIBUTION

Conceptualization: Rushikesh M. Shete, Virendra. K. Sharma.

Methodology: Rushikesh M. Shete, Virendra. K. Sharma.

Investigation: Rushikesh M. Shete, Virendra. K. Sharma.

Discussion of results: Rushikesh M. Shete, Virendra. K. Sharma.

Writing – Original Draft: Rushikesh M. Shete.

Writing – Review and Editing: Rushikesh M. Shete, Virendra. K. Sharma.

Resources: Virendra. K. Sharma.

Supervision: Virendra. K. Sharma.

Approval of the final text: Rushikesh M. Shete, Virendra. K. Sharma.

VII. ACKNOWLEDGMENTS

The support of research is provided by the Bhagwant University, Ajmer, Rajasthan, India.

VIII. REFERENCES

- [1] X. Gou et al., "A Sketch Framework for Approximate Data Stream Processing in Sliding Windows," in IEEE Transactions on Knowledge and Data Engineering, vol. 35, no. 5, pp. 4411-4424, 1 May 2023, doi: 10.1109/TKDE.2022.3151140.
- [2] S. Cheng, D. Yang, T. Yang, H. Zhang and B. Cui, "LTC: A Fast Algorithm to Accurately Find Significant Items in Data Streams," in IEEE Transactions on Knowledge and Data Engineering, vol. 34, no. 9, pp. 4342-4356, 1 Sept. 2022, doi: 10.1109/TKDE.2020.3038911.
- [3] P. Li, H. Zhang, X. Hu and X. Wu, "High-Dimensional Multi-Label Data Stream Classification With Concept Drifting Detection," in IEEE Transactions on Knowledge and Data Engineering, vol. 35, no. 8, pp. 8085-8099, 1 Aug. 2023, doi: 10.1109/TKDE.2022.3200068.
- [4] F. Zhao, S. Li, B. B. Zhou, H. Jin and L. T. Yang, "HCache: A Hash-based Hybrid Caching Model for Real-Time Streaming Data Analytics," in IEEE Transactions on Services Computing, vol. 14, no. 5, pp. 1384-1396, 1 Sept.-Oct. 2021, doi: 10.1109/TSC.2018.2874966.
- [5] Shilpika, T. Fujiwara, N. Sakamoto, J. Nonaka and K. -L. Ma, "A Visual Analytics Approach for Hardware System Monitoring with Streaming Functional Data Analysis," in IEEE Transactions on Visualization and Computer Graphics, vol. 28, no. 6, pp. 2338-2349, June 2022, doi: 10.1109/TVCG.2022.3165348.
- [6] J. Sui, Z. Liu, L. Liu, A. Jung and X. Li, "Dynamic Sparse Subspace Clustering for Evolving High-Dimensional Data Streams," in IEEE Transactions on Cybernetics, vol. 52, no. 6, pp. 4173-4186, June 2022, doi: 10.1109/TCYB.2020.3023973.
- [7] R. Miao, Z. Zhong, J. Guo, Z. Li, T. Yang and B. Cui, "BurstSketch: Finding Bursts in Data Streams," in IEEE Transactions on Knowledge and Data Engineering, vol. 35, no. 11, pp. 11126-11140, 1 Nov. 2023, doi: 10.1109/TKDE.2022.3223686.
- [8] D. Wu, Y. He, X. Luo and M. Zhou, "A Latent Factor Analysis-Based Approach to Online Sparse Streaming Feature Selection," in IEEE Transactions on Systems, Man, and Cybernetics: Systems, vol. 52, no. 11, pp. 6744-6758, Nov. 2022, doi: 10.1109/TSMC.2021.3096065.
feature;streaming feature},
- [9] Z. Fan et al., "HoppingSketch: More Accurate Temporal Membership Query and Frequency Query," in IEEE Transactions on Knowledge and Data Engineering, vol. 35, no. 9, pp. 9067-9072, 1 Sept. 2023, doi: 10.1109/TKDE.2022.3221111.
- [10] E. Curry, D. Salwala, P. Dhingra, F. A. Pontes and P. Yadav, "Multimodal Event Processing: A Neural-Symbolic Paradigm for the Internet of Multimedia Things," in IEEE Internet of Things Journal, vol. 9, no. 15, pp. 13705-13724, 1 Aug. 1, 2022, doi: 10.1109/JIOT.2022.3143171.
- [11] Z. Huang, Y. Qiu, J. Yu and G. Zhou, "Multi-Aspect Streaming Tensor Ring Completion for Dynamic Incremental Data," in IEEE Signal Processing Letters, vol. 29, pp. 2657-2661, 2022, doi: 10.1109/LSP.2022.3231469.
- [12] C. B. Mawuli et al., "FedStream: Prototype-Based Federated Learning on Distributed Concept-Drifting Data Streams," in IEEE Transactions on Systems, Man, and Cybernetics: Systems, vol. 53, no. 11, pp. 7112-7124, Nov. 2023, doi: 10.1109/TSMC.2023.3293462.
- [13] J. W. Sangma, Yogita, V. Pal, N. Kumar and R. Kushwaha, "FHC-NDS: Fuzzy Hierarchical Clustering of Multiple Nominal Data Streams," in IEEE Transactions on Fuzzy Systems, vol. 31, no. 3, pp. 786-798, March 2023, doi: 10.1109/TFUZZ.2022.3189083.
- [14] L. Yang, X. Chen, Y. Luo, X. Lan and W. Wang, "IDEA: A utility-enhanced approach to incomplete data stream anonymization," in Tsinghua Science and Technology, vol. 27, no. 1, pp. 127-140, Feb. 2022, doi: 10.26599/TST.2020.9010031.
- [15] Y. Wang et al., "Novelty Detection and Online Learning for Chunk Data Streams," in IEEE Transactions on Pattern Analysis and Machine Intelligence, vol. 43, no. 7, pp. 2400-2412, 1 July 2021, doi: 10.1109/TPAMI.2020.2965531.
- [16] J. C. Bezdek and J. M. Keller, "Streaming Data Analysis: Clustering or Classification?," in IEEE Transactions on Systems, Man, and Cybernetics: Systems, vol. 51, no. 1, pp. 91-102, Jan. 2021, doi: 10.1109/TSMC.2020.3035957.
- [17] S. Nguyen, Z. Salcic, X. Zhang and A. Bisht, "A Low-Cost Two-Tier Fog Computing Testbed for Streaming IoT-Based Applications," in IEEE Internet of Things Journal, vol. 8, no. 8, pp. 6928-6939, 15 April 15, 2021, doi: 10.1109/JIOT.2020.3036352.
- [18] E. Mehmood, T. Anees, A. S. Al-Shamayleh, A. H. Al-Ghushami, W. Khalil and A. Akhunzada, "DHSDJArch: An Efficient Design of Distributed Heterogeneous Stream-Disk Join Architecture," in IEEE Access, vol. 11, pp. 63565-63578, 2023, doi: 10.1109/ACCESS.2023.3288284.
- [19] V. Gulisano, Y. Nikolakopoulos, M. Papatriantafilou and P. Tsigas, "ScaleJoin: A Deterministic, Disjoint-Parallel and Skew-Resilient Stream Join," in IEEE Transactions on Big Data, vol. 7, no. 2, pp. 299-312, 1 June 2021, doi: 10.1109/TBDATA SAMPLES.2016.2624274.
- [20] X. Gou, L. Zou, C. Zhao and T. Yang, "Graph Stream Sketch: Summarizing Graph Streams With High Speed and Accuracy," in IEEE Transactions on Knowledge and Data Engineering, vol. 35, no. 6, pp. 5901-5914, 1 June 2023, doi: 10.1109/TKDE.2022.3174570.
- [21] C. Yang, Z. Du, X. Meng, X. Zhang, X. Hao and D. A. Bader, "Anomaly Detection in Catalog Streams," in IEEE Transactions on Big Data, vol. 9, no. 1, pp. 294-311, 1 Feb. 2023, doi: 10.1109/TBDATA SAMPLES.2022.3161925.
- [22] G. Zhang, K. Liu, H. Hu, V. Aggarwal and J. Y. B. Lee, "Post-Streaming Wastage Analysis – A Data Wastage Aware Framework in Mobile Video Streaming," in IEEE Transactions on Mobile Computing, vol. 22, no. 1, pp. 389-401, 1 Jan. 2023, doi: 10.1109/TMC.2021.3069764.
- [23] V. Gyurjyan et al., "ERSAP: Toward Better NP Data-Stream Analytics With Flow-Based Programming," in IEEE Transactions on Nuclear Science, vol. 70, no. 6, pp. 966-970, June 2023, doi: 10.1109/TNS.2023.3242548.
- [24] Y. Li, L. Zou, M. T. Özsü and D. Zhao, "Space-Efficient Subgraph Search Over Streaming Graph With Timing Order Constraint," in IEEE Transactions on Knowledge and Data Engineering, vol. 34, no. 9, pp. 4453-4467, 1 Sept. 2022, doi: 10.1109/TKDE.2020.3035902.
- [25] K. Li, J. Qiao and D. Wang, "Online Self-Learning Stochastic Configuration Networks for Nonstationary Data Stream Analysis," in IEEE Transactions on Industrial Informatics, vol. 20, no. 3, pp. 3222-3231, March 2024, doi: 10.1109/TII.2023.3301059.